

XPERT Range

Electric Storage Water Heaters



INITIO

INSTALLATION	WH/FS/HOR
HMI	No
TANK PATERIAL	Enameled (Titanium coated)
HEATING ELEMENT	Copper
ANODE	Magnesium
POWER (KW)	From 1,2 up to 3 kW
TMAX (°C)	80
CABLE	No (only <ESP> range)
DIELECTRIC JOINTS	1x metallic rotating joint (PRO)
IPX	IP25
OPR (KWH/24H)	From 0,79 up to 2,68
CONNECTIVITY	No
V40 (LT)	From 65 up to 473
TAPPING PROFILE	100 L: L; 150 L: M; >150 L: L

Initio



Electric storage water heaters

Installer friendly

- / Ultra Grip to facilitate transportation and installation.
- / Easy clip to avoid screw removal.
- / Dimensions and templates on carton box.
- / Universal kit (optional paid accessory).

Enduring Quality

- / Magnesium anode to prevent corrosion of the tank and extend lifespan.
- / Titan-shield exclusive enameling system.

MODELS	WALL-HUNG		WALL-HUNG		FLOOR STANDING
	VERT	HOR RIGHT	HOR BELOW		
100 L	Ø 513, 560 H: 835, 770	Ø 530, 570 W: 835, 760	Ø 560 W: 750	/	/
150 L	Ø 513, 560 H: 1160, 1010	Ø 513, 570 W: 1160, 1020	Ø 560 W: 1010	/	/
200 L	Ø 513, 560 H: 1463, 1280	Ø 513, 570 W: 1463, 1285	Ø 560 W: 1270	Ø 570 H: 1300	
250 L	/	/	/	Ø 570 H: 1560	
300 L	/	/	/	Ø 570 H: 1820	

